

CANGURO NORMAL SUPER

**TRINCIAERBA/ TRINCIASARMENTI
CON RACCOLTA PER TRATTORI DA 40 A 80 CV**

**PRUNING FLAIL COLLECTOR
FOR TRACTORS FROM 40 TO 80 HP**


 **YouTube**



La trinciaerba / trinciasarmenti con raccolta CANGURO NORMAL SUPER è adatta per l'applicazione a trattori da 40 a 80 CV di potenza e con attacco a 3 punti di categoria 1 (per la 1200 e 1600) e di categoria 2 (per la 1800 e 2000). Lo scarico del prodotto tagliato e raccolto nel capiente cassone, avviene a terra tramite l'ausilio di appositi pistoni idraulici. Trinciaerba solida e massiccia, è usata principalmente in presenza di erba molto alta su aree estese, parchi pubblici, zone boschive (azione di prevenzione incendi), in orticoltura e talvolta per la manutenzione agricola.

The flail mower / shredder with collection CANGURO NORMAL SUPER is suitable for application to tractors from 40 to 80 HP of power and with 3-point attachment of category 1 (for the 1200 and 1600) and category 2 (for the 1800 and 2000). The unloading of the product cut and collected in the large catcher, takes place on the ground with the help of special hydraulic pistons. Solid and massive flail mower, it is mainly used in the presence of very high grass on large areas, public parks, wooded areas (fire prevention action), in horticulture and sometimes for agricultural maintenance.



MODELLO MODEL					
	(MM)	(HP)	(KW)	Nr.	(MM)
CANGURO NORMAL 1200	1165	40 - 55	30 - 41	16	30 - 100
CANGURO SUPER 1600	1525	50 - 60	37 - 45	20	30 - 100
CANGURO SUPER 1800	1720	60 - 70	45 - 52	24	30 - 100
CANGURO SUPER 2000	1920	70 - 80	52 - 59,5	28	30 - 100



Verde pubblico
Municipality maintenance



Orticoltura
Horticulture maintenance



Manutenzione agricola
Agriculture maintenance

COMPONENTI TECNICHE DI SERIE TECHNICAL COMPONENTS STANDARD



Facile tensione cinghie.
Easy belts tightening
adjustment.



Scarico a terra mediante nr.
2 martinetti idraulici.
Ground discharge by nr. 2
hydraulic rams.

ACCESSORI ACCESSORIES



Regolazione dell'altezza
di taglio su ruote frontali
doppie.
Height of cut adjustment on
front castor double wheels.



Convogliatore per
sarmenti.
Front metal steel conveyor
for branches.


LAME STANDARD STANDARD BLADES



Mazza in acciaio forgiato e temperata per
Canguro Normal 1,2 Kg.
Forged steel and hardened hammer
for Canguro Normal 1,2 Kg.



Mazza in acciaio forgiato e temperata
Mod. Super 1,6 Kg.
Forged steel and hardened hammer
Mod. Super 1,6 Kg.

MODELLO MODEL	 LT.	 Kg	 RPM	 (LxPxH)	 (LxPxH)
	(LT)	(KG)	(RPM)	(LxPxH)	(LxPxH)
CANGURO NORMAL 1200	1100	540	595	1550 x 1400 x 2100	1555 x 1570 x 1370
CANGURO SUPER 1600	1450	540	720	1850 x 1400 x 2100	1980 x 1850 x 1370
CANGURO SUPER 1800	1600	540	820	2200 x 1400 x 2100	2180 x 1995 x 1370
CANGURO SUPER 2000	1800	540	870	2350 x 1400 x 2100	2380 x 1995 x 1370