

# ROBOFOX HYBRID

**TRINCIAERBA IBRIDA -  
RADIOCOMANDATA E CINGOLATA**  
*HYBRID REMOTE CONTROLLED  
FLAIL MOWER*

VIDEO 




## Caratteristiche

- Trincia radiocomandata ibrida.
- Robusta per manutentori del verde pubblico, agricolo e parchi fotovoltaici.
- Veloce sfalcio erba su pendenze fino a 50°.
- Portata telecomando "CE" fino a 300mt.
- Capacità taglio erba fino a 150cm di altezza.
- Sicura e confortevole.
- Bassi costi di manutenzione ed esercizio.
- Cambio olio solo ogni 500 ore di utilizzo.
- Compatta per carico su furgoni.
- Taglio arbusti fino a 3cm di diametro.
- 3 ore di autonomia di lavoro circa.

## Features

- Hybrid radio-controlled flail mower.
- Sturdy for municipality turf works, agricultural and park maintenance.
- Fast grass mowing on slopes up to 50°.
- "CE" remote control radio with range up to 300mt.
- Grass cutting capacity up to 150cm height.
- Safe and comfortable.
- Low maintenance and operating costs.
- Oil change every 500 hours of use only.
- Compact for loading onto vans.
- Cuts shrubs up to 3 cm in diameter.
- Approx. 3 hours working autonomy.



| MODELLO<br>MODEL |  |  |  |  |
|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                  | (MM)                                                                                | (HP-KW)                                                                             | "V"                                                                                   | Nr.                                                                                   |
| ROBOFOX HYBRID   | 900                                                                                 | B&S - 28 / 20                                                                       | 48                                                                                    | 24                                                                                    |
| ROBOFOX HYBRID   | 1200                                                                                | B&S - 28 / 20                                                                       | 56                                                                                    | 28                                                                                    |



## COMPONENTI TECNICHE DI SERIE TECHNICAL COMPONENTS STANDARD



Telecomando.  
Remote controller.



Cingolo con  
profilo basso.  
Low Profile  
Tracks.  
40° Max



Cingolo con  
profilo alto  
High Profile  
Tracks.  
50° Max

Mod. "H"



Hybrid  
Electra

Larghezza  
di taglio  
Cutting  
width

**900 cm**



Hybrid  
Electra

Inclinazione  
Slope

Max. **45°**



Hybrid

Larghezza  
di taglio  
Cutting  
width

**1200 cm**



Hybrid  
Electra

Mod. "L"

Max. **50°**



Cambio olio solo ogni 500 ore.  
Oil change every 500 hour only.

## ACCESSORI SU RICHIESTA ACCESSORIES ON REQUEST



Inclinometro di sicurezza.  
Safety inclinometer.



Carica batterie monofase  
50-60 Hz.  
Battery charger single phase  
50-60 Hz.  
**STANDARD: 220 V - 3 kWh**



Luci a led.  
Led lights.



Attacco traino.  
Towing Hitch.

## LAME STANDARD STANDARD BLADES




Coltello "Y" per taglio  
mulching sp. 4 mm.  
Flail "Y" for mulching  
cut with 4 mm  
thickness.

## LAME ACCESSORIE ON REQUEST BLADES



Mazzetta forgiata  
per taglio lineare e  
piccoli arbusti.  
Heavy duty cast flail  
for linear and small  
cutting shrubs.

| MODELLO<br>MODEL |  |  |  |  |
|------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|                  | (MM)                                                                                | (KG)                                                                                | (LxPxH)                                                                              | (LxPxH)                                                                               |
| ROBOFOX HYBRID   | 10 - 120                                                                            | 690                                                                                 | 2190 x 1050 x 990                                                                    | 2300 x 1140 x 1200                                                                    |
| ROBOFOX HYBRID   | 10 - 120                                                                            | 750                                                                                 | 2190 x 1330 x 990                                                                    | 2300 x 1530 x 1200                                                                    |